WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7: B32B 29/00, B65D 77/20, 65/40

A1

(11) International Publication Number:

WO 00/15431

(43) International Publication Date:

23 March 2000 (23.03.00)

(21) International Application Number:

PCT/DK99/00488

(22) International Filing Date:

15 September 1999 (15.09.99)

(30) Priority Data:

PA 1998 01160

15 September 1998 (15.09.98)

(71)(72) Applicant and Inventor: PEDERSEN, Steen [DK/DK]; Strandpromenaden 25, DK-6710 Esbjerg V (DK).

(74) Agent: PATRADE A/S; Aaboulevarden 21, DK-8000 Aarhus C (DK).

(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.


Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.


In English translation (filed in Danish).

(54) Title: PACKING TRAY AND METHOD FOR ITS PRODUCTION AND USE

(57) Abstract

There is described a packing tray (2) mainly of cardboard, paper, or a laminate, e.g. extruded, primarily containing these materials and in particular intended as sales packing for foodstuffs, e.g. meat, sliced meat or vegetables, poultry, fish, fruit, vegetables, salads, pasta, dishes for dinner, bakery and dairy products, which tray preferably has a rectangular shape with rounded corner parts (8), a mainly plane bottom (14) and sloping side walls (16) which at the top continue in an annular edge (12) approximately extending in parallel with the bottom (14), which tray (2) consists of one moulded item, the upper side of which consists of a gas- and/or diffusion-proof coating having such barrier abilities that a covering film or a dome-shaped, e.g. transparent, lid (18) may be connected gas-proof or diffusion-proof to the said annular edge by welding. There is also described a method for making and using, respectively, the packing tray.





FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

| Albania | ES | Spain | LS | Lesotho | SI | Slovenia |
|--------------------------|--|--|--|---|--|--|
| Amenia | FI | Finland | LT | Lithuania | SK | Slovakia |
| Austria | FR | France | LU | Luxembourg | SN | Senegal |
| Australia | GA | Gabon | LV | Latvia | | Swaziland |
| Azerbaijan | GB | United Kingdom | MC | Monaco | | Chad |
| Bosnia and Herzegovina | GE | Georgia | MD | Republic of Moldova | | Togo |
| Barbados | GH | Ghana | MG | | | Tajikistan |
| Belgium | GN . | Guinea | MK | • | - | Turkmenistan |
| Burkina Faso | GR | Greece | | | | Turkey |
| Bulgaria | HU | Hungary | ML | Mali | | 'Trinidad and Tobago |
| Benin | ΙE | Ireland | MN | Mongolia | | Ukraine |
| Brazil | ΊL | Israel | MR | Mauritania | | Uganda |
| Belarus | IS | Iceland | MW | Malawi | | United States of America |
| Canada | IT | Italy | MX | | | Uzbekistan |
| Central African Republic | JP | Japan | NE | | | Viet Nam |
| Congo | KE | Kenya | NI. | - | | Yugoslavia |
| Switzerland | KG | • | | | | Zimbabwe |
| Côte d'Ivoire | KP | Democratic People's | | • | 211 | Zimbaowc |
| Cameroon | | | | | | |
| China | KR | • | | | | |
| Cuba | KZ | Kazakstan | | - | | |
| Czech Republic | LC | Saint Lucia | | | | • |
| Germany | LI | Liechtenstein | | | | |
| Denmark | LK | Sri Lanka | | | • | |
| Estonia | LR | Liberia | SG | Singapore | | |
| | Armenia Austria Australia Azerbaijan Bosnia and Herzegovina Barbados Belgium Burkina Faso Bulgaria Benin Brazil Belarus Canada Central African Republic Congo Switzerland Côte d'Ivoire Cameroon China Cuba Czech Republic Germany Denmark | Armenia FI Austria FR Australia GA Azerbaijan GB Bosnia and Herzegovina GE Barbados GH Belgium GN Burkina Faso GR Bulgaria HU Benim IE Brazil IL Belarus IS Canada IT Central African Republic JP Congo KE Switzerland KG Côte d'Ivoire KP Cameroon China KR Cuba KZ Czech Republic LC Germany LI Denmark LK | Armenia FI Finland Austria FR France Australia GA Gabon Azerbaijan GB United Kingdom Bosnia and Herzegovina GE Georgia Barbados GH Ghana Belgium GN Guinea Burkina Faso GR Greece Bulgaria HU Hungary Benin IE Ireland Brazil IL Israel Belarus IS Iceland Canada IT Italy Central African Republic JP Japan Congo KE Kenya Switzerland KG Kyrgyzstan Côte d'Ivoire KP Democratic People's Cameroon Republic of Korea China KR Republic of Korea Cuba KZ Kazakstan Czech Republic LC Saint Lucia Germany LI Liechtenstein Denmark LK Sri Lanka | Armenia FI Finland LT Austria FR France LU Australia GA Gabon LV Azerbaijan GB United Kingdom MC Bosnia and Herzegovina GE Georgia MD Barbados GH Ghana MG Belgium GN Guinea MK Burkina Faso GR Greece Bulgaria HU Hungary ML Benin IE Ireland MN Brazil IL Israel MR Belarus IS Iceland MW Canada IT Italy MX Central African Republic JP Japan NE Congo KE Kenya NI Switzerland KG Kyrgyzstan NO Côte d'Ivoire KP Democratic People's NZ Cameroon Republic OF China KR Republic of Korea PL China KR Republic OF KOREA Czech Republic LC Saint Lucia RO Cermany LI Liechtenstein SD Denmark LK Sri Lanka SE | Armenia FI Finland LT Lithuania Austria FR France LU Luxembourg Australia GA Gabon LV Latvia Azerbaijan GB United Kingdom MC Monaco Bosnia and Herzegovina GE Georgia MD Republic of Moldova Barbados GH Ghana MG Madagascar Belgium GN Guinea MK The former Yugoslav Burkina Faso GR Greece Republic of Macedonia Bulgaria HU Hungary ML Mali Benin IE Ireland MN Mongolia Brazil IL Israel MR Mauritania Belarus IS Iceland MW Malawi Canada IT Italy MX Mexico Central African Republic JP Japan NE Niger Congo KE Kenya NL Netherlands Switzerland KG Kyrgyzstan NO Norway Côte d'Ivoire KP Democratic People's NZ New Zealand Cameroon Republic of Korea PL Poland China KR Republic of Korea PT Portugal Cuba KZ Kazakstan RO Romania Cermany LI Liechtenstein SD Sudan Denmark LK Sri Lanka SE Sweden | Armenia FI Finland LT Lithuania SK Austria FR France LU Luxembourg SN Australia GA Gabon LV Latvia SZ Azerbaijan GB United Kingdom MC Monaco TD Bosnia and Herzegovina GE Georgia MD Republic of Moldova TG Barbados GH Ghana MG Madagascar TJ Belgium GN Guinea MK The former Yugoslav TM Burkina Faso GR Greece Republic of Macedonia TR Bulgaria HU Hungary ML Mali TT Benin IE Ireland MN Mongolia UA Brazil IL Israel MR Mauritania UG Belarus IS Iceland MW Malawi US Canada IT Italy MX Mexico UZ Central African Republic JP Japan NE Niger VN Congo KE Kenya NL Netherlands YU Switzerland KG Kyrgyzstan NO Norway ZW Côte d'Ivoire KP Democratic People's NZ New Zealand Camano KR Republic of Korea PT Portugal Cuba KZ Kazakstan RO Romania Czech Republic LC Saint Lucia RU Russian Federation Germany LI Liechtenstein SD Sudan Denmark LK Sri Lanka SE Sweden |

Packing Tray and Method for Its Production and Use

The present invention concerns a packing tray substantially of cardboard or, for example, an extruded laminate containing these materials, and of the kind indicated in the preamble of claim 1.

This kind of packing trays are used to a very large extent as sales packings for fresh foodstuffs of almost any kind, and most often the packing tray is provided with a simple wrapping of cheap plastic film. When speaking of meat, poultry, and fish, the shelf life of such fresh goods is only very short, and according to present practice and rules, the sales period for minced meat is only one or two days. The sales period for sliced meat and fish is also only very few days, which inter alia is contributing to that almost every supermarket necessarily must have its own butchering department which is often not profitable at all out of turnover considerations only.

15

5

10

On this background, the invention has the purpose of indicating an improved packing tray which may be a contributing factor for increasing, for example, the sales period for fresh foodstuffs, e.g. meat, sliced meat and vegetables, poultry, salads and fish, and which besides also may imply other advantages.

20

25

30

The packing tray according to the invention is characterised in that it consists of one moulded item, the upper side of which consisting of a gas- and/or diffusion-proof coating having such barrier abilities that a covering film or a dome-shaped, e.g. transparent, lid may be connected gas-proof or diffusion-proof to the said annular edge by welding. By means of simple measures there is hereby achieved a packing tray which is particularly suited for packing fresh foodstuffs, e.g. meat, sliced meat and vegetables, poultry and fish, fruit, vegetables, salads, pasta, dinner dishes, bakery and dairy products. The indicated packing tray also makes possible to perform the final top sealing of the packing tray and its content with simultaneous scavenging with a protective gas with the purpose of avoiding or reducing decomposition of the foodstuff,

5

10

15

20

25

30

so that the keeping quality and hence the sales period of the foodstuffs concerned may be prolonged considerably.

In that connection it should be mentioned that the said barrier qualities of the surface coating of the packing tray according to the invention together with the used film wrapping and/or the used lids correspond to a gas- and diffusion-proof barrier film with high barrier abilities or with low gas permeability. In practice, it is almost impossible to have a coating or a film wrapping being completely impermeable to diffusion of aqueous vapour. Besides, in connection with meat, there is no real risk in practice of drying up as fresh meat gives off humidity, but still it is of great significance to minimise diffusion of humidity out of the packing tray according to the invention.

The packing tray according to the invention is suitably designed so that said annular edge is designed with a number of bending lines at least opposite to the said rounded corner parts, and that the said coating has a certain minimum thickness. In a simple way it is hereby ensured that by the final top sealing, tightness is also achieved along edge parts of the rounded corner parts provided with bending lines that extend transversely to said edge parts. The very thick coating ensures, in other words, a smoothing of local unevennesses at said corner parts because of the transversely directed bending lines, i.e. the very thick coating at the subsequent top sealing of the packing tray also contributes to improve the welding and/or melting together at the corner parts.

Advantageously, the packing tray according to the invention may be thus designed that film wrapping is a so-called peelable film, i.e. a film which is particularly easy to remove from the annular edge of the packing tray.

With the purpose of making it very spacious, the packing tray according to the invention may advantageously be thus designed so that said dome-shaped lids are constituted by a correspondingly designed, inverted tray, which trays are welded together edge to edge. In other words, the total packing consists of two identically shaped packing trays which are welded gas-proof edge to edge.

The packing tray according to the invention may be thus designed as sales packing in an advantageous way so that tray, lid and possible paper laminated extruded film wrapping are provided with printing.

Furthermore, the invention concerns a method for making a packing tray according to claim 1 out of sheet- or roll-shaped material layer of a cardboard material, which is laminated, coated or provided with coating by extrusion, the surface coating of which material is weldable, which method is characterised in that blanks of material, the shape of which correspond to the packing tray, are punched out, that preferably before a number of bending lines are embossed at corner parts of the blanks of material, and that these thereafter are moulded by means of a moulding tool, preferably a heated moulding tool. Possible projecting material is cut off the annular edge of the finished packing trays.

The method according to the invention may advantageously be modified by using a material with a very thick surface coating which at the subsequent moulding by means of heat and/or friction ensures a smoothing and melting together of the bending lines at the corner parts of the annular edge at least.

The invention also concerns a method for using a packing tray according to claim 1, for example as sales packing for foodstuffs, where one or more food item, e.g. a recently slaughtered chicken, is placed on the tray, the method being characterised in that the foodstuffs are covered by a weldable, gas-proof film which is welded to the annular edge of the packing tray, preferably with simultaneous scavenging with a protective gas.

An alternative method for using a packing tray according to claim 1, for example as sales packing for foodstuffs, where one or more food items, e.g. a portion of minced flesh or meat, is placed on the tray, characterised in that the foodstuffs are covered by means of a dome-shaped, transparent plastic lid which is welded to the annular edge of the packing tray, preferably with simultaneous scavenging with a protective gas.

15

20

25

WO 00/15431 PCT/DK99/00488

A further alternative method for using a packing tray according to claim 1, for example as sales packing for foodstuffs, e.g. prepared dinner dishes, where a portion of foodstuffs are placed on the tray, characterised in that the foodstuffs are covered by means of a dome-shaped lid consisting of a correspondingly shaped, inverted tray, and that the trays are welded together at the annular edge, preferably with simultaneous scavenging with a protective gas.

The invention is explained in more detail in the following with the drawing, on which:

Fig. 1 shows a top view of an embodiment of a packing according to the invention,

Fig. 2 shows a longitudinal section of the packing tray shown in Fig. 1, and

Fig. 3 shows a transverse section of the packing tray shown in Fig. 1.

The shown packing tray 2 has a shape known per se as the it is mainly rectangular with mutually parallel longitudinal sides 4 and short sides 6 and with rounded corner parts 8, each being designed with a large number of bending lines 10. These bending lines 10 at the corner parts 8 also extends over an annular, outward bent edge 12 which is substantially in parallel with a plane bottom 14. A slightly outward/upward sloping side wall 16 extends between this and the annular edge 12. The bending lines 10 at the corner parts 8 have the purpose of making easier to mould the packing tray 2 out of a previously punched plane blank of material without any breakage occurring in the blank which may be punched out from a sheet or roll shaped layer of material.

The packing tray 2 is made of cardboard, or preferably a laminate containing cardboard. The packing tray 2 is developed particularly for use for fresh foodstuffs, e.g. meat, sliced meat or vegetables, poultry, fish, fruit, vegetables, salads, pasta, dinner dishes, bakery and dairy products, and there is preferably used a laminated material where the core material substantially consists of cardboard that either by coating or extrusion is provided with a suitable surface coating which at the side coming into contact with the foodstuff consists of a gas-proof, weldable coating. The external side or the underside of the packing tray or the material layer may possibly be impregnated in order to make the external side or the underside less absorbing.

5

10

15

20

25

By means of the upper weldable coating of the tray 2, it becomes very easy to seal of the packing tray 2 at the top - when the foodstuff has been placed on this - by means of a gas-proof, weldable plastic film extending over the foodstuff, e.g. a chicken, and which is welded to the annular edge 12 while scavenging with a protective gas, so that an efficiently sealed and presentable sales packing with exceptionally long keeping qualities (shelf life) is formed.

The welding together may take place by means of a welding tool with a welding sole with a protruding edge so that welding together only takes place along the edge, or there may be used a plane welding plate. In order to ensure that welding is made correctly and gas-proof also at the corner parts 8 with the bending lines 10, welding soles or welding plates with mutually co-operating projecting edges, grooves or lamellae may be used.

15

10

5

In Fig. 2 showing a longitudinal section through the packing tray 2, there is furthermore shown with stippled line that two identically shaped packing trays 2 welded together edge to edge may form a packing with a relatively large capacity.

20

In Fig. 3 showing a cross section through the packing tray 2, there is furthermore shown with stippled line that the packing tray 2 may be provided with a preferably rigidly dome-shaped lid 18 which, for example, may be transparent and printed.

25

The surface coating of the packing tray may advantageously consist of several layers, namely a lower hard cardboard layer and an upper soft weld layer which during the moulding process melts together by means of heat or friction so that also the bending lines in the corner areas are smoothed out with certainty and welded together in a gasproof way.

30

For use as packing for prepared dinner dishes and other foodstuffs like pizzas and other dough items which are often cooked in a microwave oven, it may be suitable that at least the side of the cardboard or paper material constituting the inner side of the

packing tray is coated with a susceptor coating consisting of a hard plastic layer, e.g. PET or PEN, toward the cardboard or paper material, and which at the opposite side consist of a soft weld coating. Thereby it is possible to achieve longer shelf life and at the same time a faster and more even baking in the microwave oven. It may also be advantageous that the lid at the inner side is provided with a susceptor coating.

It should be mentioned that it is within the scope of the invention to design the packing tray with any other form than the described substantially rectangular shape. For example, the packing tray according to the invention could be designed with substantially circular or substantially elliptical shape. A possible alternative form of the packing tray according to the invention could be designing the tray with several compartments which even could be arranged to be individually sealed with one of the said coverings, possibly including scavenging with protective gas during the sealing procedure.

15

10

CLAIMS

5

10

- 1. A packing tray (2) substantially of cardboard, paper, or a laminate made, for example, by extrusion and based on cardboard or paper and in particular intended as sales packing for foodstuffs, e.g. meat, sliced meat or vegetables, poultry, fish, fruit, vegetables, pasta, salads, dishes for dinner, bakery and dairy products, which tray preferably has a rectangular shape with rounded corner parts (8), a mainly plane bottom (14) and sloping side walls (16) which at the top continue in an annular edge (12) approximately extending in parallel with the bottom (14), c h a r a c t e r i s e d in that the tray (2) consists of one moulded item, the upper side of which consist of a gas- and/or diffusion-proof coating having such barrier abilities that a covering film or a domeshaped, e.g. transparent, lid (18) may be connected gas-proof or diffusion-proof to the said annular edge by welding.
- 2. A packing tray (2) according to claim 1, c h a r a c t e r i s e d in that the said annular edge (12) is designed with a number of bending lines (10) at least opposite to the said rounded corner parts (8), and that the said coating has a certain minimum thickness.
- 3. A packing tray (2) according to claim 1, c h a r a c t e r i s e d in that the said film wrapping is a so-called peelable foil, i.e. a foil which is exceptionally easy to remove from the annular edge (12) of the packing tray.
- 4. A packing tray (2) according to claim 1, characterised in that the said dome-shaped lid is constituted by a correspondingly designed, inverted tray (2), which trays are welded together edge to edge.
 - 5. A packing tray according to claim 1 4, c h a r a c t e r i s e d in that tray (2), lid (18) and possible paper laminated extruded film wrapping is provided with print.
 - 6. A method for making a packing tray according to claim 1 out of sheet- or roll-shaped material layer of a cardboard material, which is laminated, coated or provided

WO 00/15431 PCT/DK99/00488

with coating by extrusion, the surface coating of which material is weldable, c h a r a c t e r i s e d in that blanks of material, the shape of which correspond to the packing tray, are punched out, that preferably at the same time a number of bending lines are embossed at corner parts of the blanks of material, and that these thereafter are moulded by means of a moulding tool, preferably a heated moulding tool.

- 7. A method according to claim 5, c h a r a c t e r i s e d in that there is used a material with an exceptionally thick surface coating which at the subsequent moulding by means of heat and friction ensures a smoothing and melting together of the bending lines at the corner parts of the annular edge at least.
- 8. A method for using a packing tray according to claim 1, for example as sales packing for foodstuffs, where one or more food item, e.g. a recently slaughtered chicken, is placed on the tray, c h a r a c t e r i s e d in that the foodstuffs are covered by a weldable, gas-proof film which is welded to the annular edge of the packing tray, preferably with simultaneous scavenging with a protective gas.
- 9. A method for using a packing tray according to claim 1, for example a sales packing for foodstuffs, where one or more food items, e.g. a portion of minced flesh or meat, is placed on the tray, c h a r a c t e r i s e d in that the foodstuffs are covered by means of a dome-shaped, transparent plastic lid which is welded to the annular edge of the packing tray, preferably with simultaneous scavenging with a protective gas.
- 10. A method for using a packing tray according to claim 1, for example as sales packing for foodstuffs, e.g. prepared dinner dishes, where a portion of foodstuffs are placed on the tray, c h a r a c t e r i s e d in that the foodstuffs are covered by means of a dome-shaped lid consisting of a correspondingly shaped, inverted tray, and that the trays are welded together at the annular edge, preferably with simultaneous scavenging with a protective gas.

5

10

15

PCT/DK99/00488






Fig. 1





International application No.

PCT/DK 99/00488 A. CLASSIFICATION OF SUBJECT MATTER IPC7: B32B 29/00, B65D 77/20, B65D 65/40 According to International Patent Classification (IPC) or to both national classification and IPC B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC7: B65D, B32B Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched SE, DK, FI, NO classes as above Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) C. DOCUMENTS CONSIDERED TO BE RELEVANT Category* Citation of document, with indication, where appropriate, of the relevant passages Relevant to claim No. X US 5418008 A (BARRY G. CALVERT), 23 May 1,2,5-10 (23.05.95)X WO 9801363 A1 (W.R. GRACE & CO. - CONN.), 1,3,6-10 15 January 1998 (15.01.98) X WO 9427868 A2 (WORLD CLASS PACKAGING SYSTEMS, 1,4,6-10 INC.), 8 December 1994 (08.12.94) Α GB 2280416 A (PRINT DESIGN & GRAPHICS LIMITED), 1-10 1 February 1995 (01.02.95) χl Further documents are listed in the continuation of Box C. See patent family annex. Special categories of cited documents: later document published after the international filing date or priority "A" document defining the general state of the art which is not considered to be of particular relevance date and not in conflict with the application but cited to understand the principle or theory underlying the invention "E" erlier document but published on or after the international filing date "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) document of particular relevance: the claimed invention cannot be document referring to an oral disclosure, use, exhibition or other considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art document published prior to the international filing date but later than the priority date claimed "&" document member of the same patent family Date of the actual completion of the international search Date of mailing of the international search report 28 January 2000 (28.01.00) 19 January 2000 Name and mailing address of the ISA/ Authorized officer Swedish Patent Office

Ellen Setréus/EÖ

Telephone No. + 46 8 782 25 00

Facsimile No. +46 8 666 02 86

Box 5055, S-102 42 STOCKHOLM

International application No. PCT/DK 99/00488

| | 701/01/33/ | |
|------------|--|-----------------------|
| C (Continu | ation). DOCUMENTS CONSIDERED TO BE RELEVANT | |
| Category* | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
| A | EP 0419068 A2 (WESTVACO CORPORATION), 27 March 1991 (27.03.91) | 1-10 |
| A | EP 0729900 A2 (GRACE S.A.), 4 Sept 1996 (04.09.96) | 1-10 |
| A | EP 0431348 A1 (PKL VERPACKUNGSSYSTEME GMBH), 12 June 1991 (12.06.91) | 1-10 |
| A | GB 2123786 A (BOWATER PACKAGING LIMITED), 8 February 1984 (08.02.84) | 1-10 |
| A | US 4026458 A (JERALD A. MORRIS ET AL), 31 May 1977 (31.05.77) | 1-16 |
| A | US 3863832 A (ROBERT L. GORDON ET AL), 4 February 1975 (04.02.75) | 1-10 |
| A | US 5425972 A (BARRY G. CALVERT), 20 June 1995 (20.06.95) | 1-10 |
| | | |
| | | |
| | | • |
| | | |
| - | | |
| | | |

Information on patent family members

02/12/99

International application No. PCT/DK 99/00488

| | atent document d in search repo | rt | Publication date | | Patent family member(s) | Publication date |
|------------|------------------------------------|----------|------------------|-----------|----------------------------|------------------|
| | · | | | <u> </u> | | |
| US | 5418008 | A | 23/05/95 | AU | 666632 B | 15/02/96 |
| | | | | AU | 1136395 A | 17/08/95 |
| | | | | CA | 2140597 A | 25/07/95 |
| | | | | CZ | 9500141 A | 13/08/97 |
| | | | | EP | 0664358 A | 26/07/95 |
| | | | | FI | 950308 A | 25/07/95 |
| | | | | HU | 73640 A | 28/08/96 |
| | | | | HU | 9500214 D | 00/00/00 |
| | | | | JP | 7267242 A | 17/10/95 |
| | | | | NO | 950205 A | 25/07/95 |
| | | | | PL | 306938 A | 07/08/95 |
| | | | | US | 5425972 A | 20/06/95 |
| | | | | CA | 2121309 A | 17/10/94 |
| | | | | EP | 0622310 A | 02/11/94 |
| | | | | JP | 7052944 A | 28/02/95 |
| WO 9801363 | A1 | 15/01/98 | AU | 3939797 A | 02/02/98 | |
| | | | | CA | 2259904 A | 15/01/98 |
| | | | EP | 0912417 A | 06/05/99 | |
| WO 9427868 | 9427868 | A2 | 08/12/94 | AU | 688329 B | 12/03/98 |
| | | | | UA | 6952094 A | 20/12/94 |
| | | | | CA | 2163230 A | 08/12/94 |
| | | | • | CA | 2261199 A | 08/12/94 |
| | | | | EP | 0699157 A | 06/03/96 |
| | | | | ΕP | 0899209 A | 03/03/99 |
| | | | | EP | 0949147 A | 13/10/99 |
| | | | | JP | 8510708 T | 12/11/96 |
| | | | | NZ | 267278 A | 24/11/97 |
| | | | ÜS | 5334405 A | 02/08/94 | |
| | | | US | 5348752 A | 20/09/94 | |
| | | | US | 5439132 A | 08/08/95 | |
| | | | US | 5447736 A | 05/09/95 | |
| | | | | US | 5901848 A | 11/05/99 |
| | | | US | 5916614 A | 29/06/99 | |
| | | | US | 5419096 A | 30/05/95 | |
| | | | US | 5509252 A | 23/04/96 | |
| | | | | | | |
| | | | US | 5529178 A | 25/06/96 | |
| | | | | US | 5419097 A | 30/05/95 |
| | | | | US | 5479759 A | 02/01/96 |
| | | | | US | 5689937 A | 25/11/97 |
| В | 2280416 | Α | 01/02/95 | GB | 9413802 D | 00/00/00 |

Form PCT/ISA/210 (patent family annex) (July 1992)

Information on patent family members

02/12/99

International application No. PCT/DK 99/00488

| | | | | | | | |
|----|---------------------------------|-----------|---------------------|------------|----------------------------|-----|------------------|
| | ent document n search report | | Publication date | | Patent family member(s) | | Publication date |
| | | | <u> </u> | L <u> </u> | | | L |
| EP | 0419068 | A2 . | 27/03/91 | SE | 0419068 | T3 | |
| | | | _ | CA | 2024151 | A.C | 23/03/91 |
| | | | | DE | 69023089 | | 18/04/96 |
| | | | | DK | 419068 | | 27/11/95 |
| | | | | | | | |
| | | | | JP | 2799317 | | 17/09/98 |
| | | | | JP | 2926650 | В | 28/07/99 |
| | | | | JP | 3120034 | A | 22/05/91 |
| | | | | JP | 8207174 | | 13/08/96 |
| | | | | | | | |
| | | | | NO | 304301 | | 30/11/98 |
| | | | | NO | 903949 | D | 00/00/00 |
| | | | | US | 5009939 | A | 23/04/91 |
| | | | | ÜS | 5169470 | | 08/12/92 |
| | | | | | | | 10/00/00 |
| EP | 0729900 | A2 | 04/09/96 | AU | 708807 | | 12/08/99 |
| | | | | AU | 4562496 | A | 05/09/96 |
| | | | | BR | 9600856 | | 30/12/97 |
| | | | | CA | 2170692 | | 02/09/96 |
| | | | | | | | |
| | | | | JP | 9095308 | | 08/04/97 |
| | | | | NZ | 286078 | A | 26/06/98 |
| | | | | US | 5744181 | A | 28/04/98 |
| | | | | ZA | 9601490 | | 16/07/96 |
| | | | | | | | |
| EP | 0431348 | A1 | 12/06/91 | DE | 3940161 | | 06/06/91 |
| | | | | DE | 3940162 | Α . | 06/06/91 |
| GB | 2123786 | Α | 08/02/84 | NON | E . | | |
| US | 4026458 | | 31/05/77 | CA | 1031709 | A | 23/05/78 |
| | | | | | | | 20 /06 /74 |
| US | 3863832 | Α | 04/02/75 | BE | 808927 | | 20/06/74 |
| | | | | CA | 994305 | | 03/08/76 |
| | | | | DE | 2363517 | Α | 04/07/74 |
| | | | | FR | 2211927 | A | 19/07/74 |
| | | | | GB | 1450813 | | 29/09/76 |
| | | | | | | | |
| | | | | IT | 1050469 | | 10/03/81 |
| | | | | JP | 1130154 | С | 17/01/83 |
| | | | | JP | 49101183 | Α | 25/09/74 |
| | | | | JP | 57022819 | | 15/05/82 |
| | | | | | 69044 | | 11/04/75 |
| | | | | LU | 09044 | | 11/04//3 |
| US | 5425972 | A | 20/06/95 | AU | 666632 | В | 15/02/96 |
| - | J | | ==• = •• = = | AU | 1136395 | | 17/08/95 |
| | | | | CA | 2140597 | | 25/07/95 |
| • | | | | | | | 13/08/97 |
| | | | | CZ | 9500141 | | |
| | | | | EP | 0664358 | | 26/07/95 |
| | | | | FI | 950308 | A | 25/07/95 |
| | | | | HŨ | 73640 | | 28/08/96 |
| | | | | | | | 00/00/00 |
| | • | | | HU | 9500214 | | |
| | | | | JP | 7267242 | | 17/10/95 |
| | - | | | NO | 950205 | Α | 25/07/95 |
| | | | | PL | 306938 | | 07/08/95 |
| | | | • | | | | 23/05/95 |
| | | | • | US | 5418008 | | |
| | | | | CA | 2121309 | | 17/10/94 |
| | | | • | EP | 0622310 |) A | 02/11/94 |
| | | | | | | | 40 /40 /05 |
| | | | | JP | 7052944 | A | 28/02/95 |

•